

## ALUMINIUM PNEUMATIC AIR-CYLINDER TUBES

NOMINAL WIDTH (MM)	D	X	W	KG/M	YOUR NOTES
12	16	x	2,0	0,238	
16	20	x	2,0	0,305	
20	25	x	2,5	0,477	
25	28	x	1,5	0,337	
25	30	x	2,5	0,583	
30	35	x	2,5	0,689	
32	35	x	1,5	0,426	
32	36	x	2,0	0,577	
40	44	x	2,0	0,713	
40	45	x	2,5	0,901	
50	54	x	2,0	0,882	
50	55	x	2,5	1,113	
63	67	x	2,0	1,103	
63	68	x	2,5	1,389	
70	76	x	3,0	1,858	
80	85	x	2,5	1,749	
80	86	x	3,0	2,112	
100	105	x	2,5	2,174	
100	106	x	3,0	2,621	
125	130	x	2,5	2,704	
125	132	x	3,5	3,815	
140	150	x	5,0	6,150	
150	160	x	5,0	6,574	
160	167	x	3,5	4,854	
160	170	x	5,0	6,998	
200	210	x	5,0	8,694	
250	262	x	6,0	13,029	
320	336	x	8,0	22,258	

### SPECIFICATION

Type	Aluminium Pneumatic Air-Cylinder Tube
Alloy	EN AW-6063 T6
Inside diameter tolerance	ISO H9-H11
Roughness	Ra <= 0,6 µm
Outside surface	Inside / Outside hardanodized, thickness 20 µm, hardness 420 HV
Straightness	0,8 mm / 1000 mm